In accordance with 91/155/EEC

Trade name: epros®FibreGlassMat CRF(+) 1050 g/m²

Material No.: Date revised: 13.10.2014 Specification: Version: 1.5 / EN

Page 1/5

Date printed: 11.11.2014

#### 01. **Product or Preparation and Company Identification**

Trade name:

epros®FibreGlassMat CRF(+) 1050 g/m<sup>2</sup>

# Product/preparation identification

Fibreglass mat for sewer rehabilitation works

### Manufacturer/supplier

Trelleborg Pipe Seals Duisburg GmbH Dr.-Alfred-Herrhausen-Allee 36 D - 47228 Duisburg

# Information department

Tel: +49 (0) 2065/999-0 Fax: +49 (0) 2065 999-111

# **Emergency call**

+49 (0) 2065/999-150

#### 02. Composition/information on ingredients

### Chemical identification

Substance

Manufacture: Glass filament roving, continuous, mechanically drawn and provided with a size finish. Then converted into a fabric and mat with both layers being subsequently sewn.

# **Ingredients**: Continuous glass filaments

An aluminoborosilicate glass / calcium aluminosilicate glass according to DIN 1259 Part 1 for general manufacture of glass-reinforced plastics and acid-proof applications.

Glass percentage > 99%

Size percentage < 1% (silane finish)

#### 03. Potential hazards

Small broken filaments may potentially cause short-term irritations to the eyes, skin or respiratory tracts.



In accordance with 91/155/EEC

Trade name: epros®FibreGlassMat CRF(+) 1050 g/m²

Material No.:

Date revised: 13.10.2014 Specification: Version: 1.5 / EN

Page 2/5

Date printed: 11.11.2014

#### 04. First aid measures

### Difficult breathing

Leave the location.

### Skin irritation

Wash the affected skin with lukewarm water and soap; no rubbing.

### Eye irritation

Wash the eyes with clear water for several minutes.

## Other allergies

Leave the location.

#### 05. Fire fighting measures

Textile glass filaments are not flammable, only the package is flammable. Suitable fire fighting agents are water, foam or powder.

#### 06. Accidental release measures

### Personal precautions

not applicable

# **Environmental precautions**

The product causes no environmental risks. For waste disposal, respect the local waste management regulations. The residual waste regulations shall apply.

### Cleaning/take-up

No special regulations or rules need to be respected.

#### 07. Handling & storage

### Handling:

Persons with increased sensibilisation for skin irritations are recommended to avoid skin contact. No rubbing!

### Storage information

The material should be stored in its original packing in a dry place and kept from direct sunlight. The recommended storage temperatures are between 10°C and 35°C, and the recommended relative humidity of air is between 40 % and 70 %.



Specification:

In accordance with 91/155/EEC

Trade name: epros®FibreGlassMat CRF(+) 1050 g/m²

Date printed: 11.11.2014

Material No.:

Date revised: 13.10.2014

Version: 1.5 / EN

Page 3/5

# 08. <u>Exposure limits and controls / Personal protective equipment</u>

# Additional information on the design of technical plants

No special recommendations under normal conditions of use. In case of high loads, exhaust plants can be installed.

Ingredients requiring occupational exposure limits to be controlled: not applicable

Personal protective equipment:

Clothing: No special measures required, but avoid worn-off spots.

Respiratory protection: No special measures required, but a paper mask could be used

(protection degree 1).

**Eye protection:** No special measures required, but safety goggles may be advisable. **Other measures:** No special measures required, but a skin ointment may be advisable.

# 09. <u>Physical & chemical properties</u>

Appearance:

Form: Woven glass roving and powder-bonded glass mat, sewn together into a flat sheet material

complex wound into rolls.

Colour: white Odour: odourless

Safety-related data:

**pH** not applicable

Change of state: Softening point: approx. 700 / 900 °C

Melting point: approx. 1100 / 1140°C

Flash point: not applicable

**Inflammability:** only the size finish and the sewing yarn decompose at 400°C and

above

Ignition temperature: not applicable Self-inflammability: not applicable

**Explosive limit**: upper limit: not applicable lower limit: not applicable

Vapour pressure: not applicable Density: 2.61 g/cm<sup>3</sup>

**Further information** 

Solubility: insoluble in water



In accordance with 91/155/EEC

Trade name: epros®FibreGlassMat CRF(+) 1050 g/m²

Material No.:

Date revised: 13.10.2014 Specification: Version: 1.5 / EN

10. Stability & reactivity

> Hazardous reactions: Complex acid-proof mat and fabric are

> > products that cannot cause any hazardous

Page 4/5

Date printed: 11.11.2014

reactions.

Hazardous decomposition products: not applicable

#### 11. **Toxicological information**

The product contains no toxic or hazardous substances or preparations under the German hazmat regulations or under § 3 of the German Chemicals Act.

It is important to know that these fibres are not inhalable and therefore cannot have any carcinogenic effect. This is attributable to the fact that they exceed 3 µm in diameter and thus are specified outside the limits set out for inhalable fibres.

Section 2.3 of the German Technical Rules Hazardous Material (TRGS 905), as issued in June 1997, is not applicable.

No. 4 of the Technical Rules TRGS 521 – fibre dusts –, as issued in May 2002, shall be observed as to the general principles of occupational hygiene for fibres with a diameter >3µm that may be generated or released during processing operations.

#### 12. **Ecological information**

This product causes no ecological risks, but it is not biodegradable.

#### 13. **Disposal considerations**

Description: Waste glass-based fibrous materials

According to the waste management regulations, waste code EWC 101103.



In accordance with 91/155/EEC

Trade name: epros®FibreGlassMat CRF(+) 1050 g/m²

Material No.: Date revised: 13.10.2014
Specification: Version: 1.5 / EN

Page 5/5

Date printed: 11.11.2014

### 14. <u>Transport information</u>

Land transport Class / section / letter

Warning sign Hazard No.: UN No.: Not applicable. unot applicable

Waterway transport Class / section / letter

Not applicable. not applicable

Sea transport Class

Not applicable. not applicable

Air transport Class

Not applicable. not applicable

### **Further information**

Complex acid-proof mat and fabric are no hazardous material under the German hazmat regulation (GGVS).

Trelleborg epros GmbH advises to transport, handle and store the product in a dry condition and in its original packaging.

# 15. Regulatory information

### Identification according to European directives

No labelling duty for the product under the German hazmat regulations.

The product contains R-phrases: not applicable

S-phrases: not applicable

Further information: none

### National Regulations (Germany)

Information on limited occupational exposure: none

Regulation on Disruption of Operations: not applicable Vbf regulation on flammable liquids: not applicable Water Hazard Class: not applicable

Other regulations, restrictions, limitations: none

### 16. Other information

### Important:

The information and data contained herein reflect the current state of our technical knowledge. They do not describe quality features and do not release any party handling the fibreglass complex from its own responsibility or its duty to comply with laws and statutory requirements.

