

NPC – Diamond Tipped Core Drills

Data Sheet

Features of NPC – Diamond Tipped Core Drills

- Designed for concrete, clay and ductile iron pipe.
- Accurate cored openings manufactured to Kor-N-Seal® specifications.
- Manufactured to meet specific cutting requirements.
- Designed, formulated, and manufactured in-house – Milford, New Hampshire, USA
- Only new, premium quality diamonds are used.
- Fast, efficient drilling.
- Close tolerance allowing trouble-free seal installation.



Coring Machine Type	Pipe/ Manhole	Core Drill	Core Drill Coupling	Diameter Range Inches [millimeters]	Recrown Service Available
Portable - Vertakor® 1200 Series	Concrete Ductile Iron Clay	Diamond	C-Flange 2" Pilot - 3 bolt	2 to 20 [51 - 508]	Yes
In-Plant – Hydrokor Series	Concrete	Diamond	A-Flange 5" Pilot - 4 bolt	2 to 62 [51 - 1575]	Yes

Recrown Services:

Diamond core drill recrown services are available. To be recrowned, the core drill barrel must be in reusable condition. Services include:

- Initial inspection
- Barrel reconditioning
- New segment installation
- Repainting
- Quality control inspection
- Prepaid overland return freight.

A recrowned core drill is 30% less than the cost of a new new diamond core drill.

Quick Change Adapter:

Quick-Change Adapters are available for our A-Flange core drills. They greatly reduce core drill change time and are designed to fit NPC Hydrokor coring machines.

Call customer service for more information. 1-800-626-2180.