


ZEPHIR S

CONSTRUCTION & ENVIRONMENT

Evacuation and material handling hoses



Applications

For suction of light industrial debris and dust.
Suitable for conveying small particles and moderately abrasive materials.

Advantages

- Very light weight and easy to handle.
- Excellent bending radius and flexibility.
- Very good crush resistance.

Technical description

Inner tube: wear resistant NR, beige, smooth.
Reinforcement: synthetic textile, cords, with embedded steel helix.
Cover: rubber coated fabric, white, corrugated.
Temperature range: - 30 °C to + 70 °C.



ZEPHIR S

07/09/2010

ID		Wall thickness		OD		Max vacuum	Bending radius	Weight	Length	Article number	Stock (■) or min. order
mm		mm	mm	mm	mm	bar	mm	kg/m	m		m
30.0	± 1.5	4.5	± 0.75	39.0	± 1.5	0.8	150	0.50	10	0126702	20
35.0	± 1.5	4.5	± 0.75	44.0	± 1.5	0.8	175	0.57	10	0123919	20
40.0	± 1.5	4.5	± 0.75	49.0	± 1.5	0.8	200	0.63	10	0074118	20
50.0	± 1.5	4.5	± 1.0	59.0	± 2.0	0.8	250	0.79	10	0201844	■
60.0	± 1.5	4.5	± 1.0	69.0	± 2.0	0.8	300	0.90	10	0201845	20
70.0	± 1.5	4.5	± 1.0	79.0	± 2.0	0.8	350	1.02	10	0074130	20
80.0	± 1.5	5.5	± 1.0	91.0	± 2.0	0.8	400	1.46	10	0201846	■
100.0	± 1.5	5.5	± 1.0	111.0	± 2.0	0.8	500	1.79	10	0201847	■
105.0	± 1.5	5.5	± 1.0	116.0	± 2.0	0.8	525	1.84	10	0070668	20
115.0	± 1.5	5.5	± 1.0	126.0	± 2.0	0.8	575	2.00	10	0070553	20
125.0	± 1.5	5.5	± 1.0	136.0	± 2.0	0.8	625	2.23	10	0095689	■
150.0	± 1.5	7.0	± 1.0	164.0	± 2.0	0.8	750	3.76	10	0202128	■

No branding

