

MATERIAL SAFETY DATA SHEET – Intek UMI-1075

SECTION 1: PRODUCT IDENTIFICATION

CAS Number: Mixture / None Assigned
 Product Name: UMI 1075
 Generic Name: Fiberglass Wool Product
 Chemical Name: Mixture
 Formulation: Mixture
 Address: Trelleborg Applied Technologies
 Trinity Park
 Randall Way
 Retford
 DN22 7AX UK
 Telephone: 44 (0) 1777 712500
 Fax: 44 (0) 1777 707001
 Email: appliedtechnologies@trelleborg.com

SECTION 2: INGREDIENTS

INGREDIENT NAME	CAS NUMBER	PERCENT	EXPOSURE LIMITS
Fiberglass Wool	65997173	15 to 95	1 fiber/cc TWA (ACGIH) 5mg/m3 TWA respirable fraction 15 mg/m3 total dust (OSHA)
Urea extended PhenolFormaldehyde Resin (cured)	N/A (Mixture)	02 to 35	Not established
Urea extended Melamine Resin (cured)	N/A (Mixture)	00 to 04	Not established
Silicone emulsion	N/A (Mixture)	00 to 08	Not established
Fiberglass Cloth Facing	N/A (Mixture)	00 to 80	Not established

SECTION 3: HAZARD IDENTIFICATION

EMERGENCY OVERVIEW: Fibrous glass material with or without fiberglass cloth facing having no significant odor. Under normal conditions of use this product is not expected to create any unusual emergency hazards. Inhalation of excessive amounts of dust from the product may cause temporary upper respiratory irritation and/or congestion. Remove affected individuals to fresh air. Skin irritation may be treated by gently washing affected area with soap and warm water. Eye irritation may be treated by flushing eyes with large amounts of water. If irritation persists, contact physician. In the event of fire use normal fire fighting procedures to prevent inhalation of smoke and gas.

POTENTIAL HEALTH EFFECTS SUMMARY: Breathing dust from this product may cause a scratchy throat, congestion and slight coughing. Getting dust or fibers on the skin or in the eyes may cause itching, rash or redness.

ACUTE (SHORT TERM) HEALTH EFFECTS: Dust from this product is a mechanical irritant that means that it may cause irritation or scratchiness of the throat and/or itching of the eyes and skin.

CHRONIC (LONG TERM) EFFECTS: See Section 11 of this MSDS.
TARGET ORGANS: Throat, lungs, skin and eyes.

SECTION 3: HAZARD IDENTIFICATION Continued

PRIMARY ROUTES OF ENTRY (EXPOSURE): Inhalation (breathing dust or fiber) and skin and eye contact.
MEDICAL CONDITIONS THAT MAY BE AGGRAVATED: Preexisting chronic respiratory, skin or eye disease or condition.

SYMPTOMS OF OVEREXPOSURE INHALATION: Irritation of upper respiratory tract (scratchy throat), coughing and congestion may occur in extreme exposure.

SKIN: Temporary irritation (itching) or redness may occur.
ABSORPTION: Not applicable.

INGESTION: This product is not intended to be ingested or eaten under normal conditions of use. If ingested, it may cause temporary irritation to the gastrointestinal (GI) tract, especially the stomach.

EYE: Temporary irritation (itching) or redness may occur.

SECTION 4: FIRST AID MEASURES

INHALATION: Remove to fresh air. Drink water to clear throat. Blow nose to remove dust and fibers.

SKIN: Wash gently with soap and warm water to remove material. Wash hands before eating or using the restroom.

ABSORPTION: Not applicable.

INGESTION: Product is not intended to be ingested or eaten. If this product is ingested, irritation of the gastrointestinal (GI) tract may occur and should be treated symptomatically. Rinse mouth with water to remove fibers and drink plenty of water to help reduce the irritation. No chronic effects are expected following ingestion.

EYE: Do not rub or scratch eyes. Dust particles may cause the eyes to be scratched. Flush eyes with large amounts of water for 5 – 15 minutes. If irritation persists, contact physician.

NOTE TO PHYSICIAN: This product is a mechanical irritant and is not expected to produce chronic health effects from acute exposure. Treatment should be directed to ward removing the source of irritation with symptomatic treatment if necessary.

SECTION 5: FIRE FIGHTING MEASURES

SUMMARY: No special procedures are expected to be necessary for this product. Normal fire fighting procedures should be followed to avoid inhalation of smoke and glass.

UNUSUAL FIRE / EXPLOSION HAZARDS: There is no potential for fire or explosion.

EXTINGUISHING MEDIA: Carbon Dioxide (CO₂), water, water fog, dry chemical.

FLAMMABILITY PROPERTIES:

Flash Point:	Not applicable
FP Test Method:	Not applicable
Flammability Limits:	Not applicable
Flame Classification:	Not determined
Flame Propagation:	Not determined
Auto ignition Temperature:	Not determined
Decomposition Temperature:	Not determined

EXPLOSIVE LIMITS:

Lower Explosive Limit:	Not applicable
Upper Explosive Limit:	Not applicable

SECTION 6: ACCIDENTAL SPILL / RELEASE MEASURES

CONTAINMENT PROCEDURES: Pick up large pieces. Vacuum dust. If sweeping is necessary, use a dust suppressant such as water. Do not dry sweep dust accumulation. These procedures will help to minimize potential exposures.

DISPOSAL: Wastes are not hazardous as defined by the Resource Conservation and Recovery Act (RCRA; 40 CFR 261). Comply with state and local regulations for disposal of fiberglass wool products. If unsure of regulations, contact local Public Health Department or the local offices of the Environmental Protection Agency(EPA).

SECTION 7: HANDLING AND STORAGE

STORAGE / HANDLING: Use protective equipment as described in SECTION 8 of this MSDS when handling uncontained material. Warehouse storage should be in accordance with any package directions. Material should be kept dry and protected from the elements.

SECTION 8: EXPOSURE CONTROL / PERSONAL PROTECTION

SUMMARY: Protective equipment should be provided as necessary to prevent irritation of the throat, eyes and skin and to keep exposure below the applicable exposure limits identified in SECTION 2 of this MSDS.

EYE: Safety glasses with side shields are recommended to keep dust and fibers out of the eyes.

SKIN: Leather or cotton gloves should be worn to prevent skin contact and irritation. Barrier creams may also be used to reduce skin contact and irritation caused by fiberglass.

RESPIRATORY: A respirator should be used if ventilation is unavailable or is inadequate for keeping dust and fiber levels below the applicable exposure limits. In those cases, use NIOSH certified disposable or reusable particulate respirator with efficiency rating of N95 or higher (under 42 CFR 84) when working with this product. For exposures up to five times the established exposure limits use a quarter mask respirator rated N95 or higher. For exposures up to ten times the established exposure limits use a half mask respirator (e.g. MSA DM11, Racad Delta N95, 3M 8210) rated N95 or higher.



SECTION 8: EXPOSURE CONTROL / PERSONAL PROTECTION Continued

Operations such as sawing, blowing, tear out and spraying may generate airborne fiber concentration requiring higher level of respiratory protection. For exposures up to 50 times the established exposure limits use a full-face respirator rated N99 or higher.

VENTILATION:	Local exhaust ventilation should be provided at areas of cutting to remove airborne fibers. General dilution ventilation should be provided as necessary to keep airborne dust and fibers below the applicable exposure limits and guide lines. The need for ventilation systems should be evaluated by a professional industrial hygienist. The Design of specific ventilation systems should be conducted by a professional engineer.
OTHER:	Loose fitting, long sleeve clothing should be worn to protect skin from irritation. Exposed skin areas should be washed with soap and warm water after handling or working with fiberglass. Clothing should be washed separately from other clothes. The washer should be rinsed thoroughly (run empty for a complete wash cycle). This will reduce the chance of fiberglass being transferred to other clothing.
SPECIAL CONSIDERATION FOR REPAIR / MAINTENANCE OF CONTAMINATED EQUIPMENT:	Use personal protective equipment as discussed above. Where possible, use a vacuum cleaner before repair / maintenance to remove excessive dust and loose fiber.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PROPERTIES:

Boiling Point:	Not determined
Evaporation Rate (Butyl acetate = 1):	Not determined
Melting Point:	>704 °C / 1300 °F
pH:	Not applicable
Saturation in Air (%):	Not applicable
Solids Content:	Not applicable
Specific Gravity (Water = 1):	Not applicable
Vapor Density (Air = 1):	Not applicable
Vapor Pressure:	Not applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES Continued

VOCs (g/liter):	Not applicable
Volatile by Volume (%):	0
Water Solubility (%):	Nil

APPEARANCE AND ODOR: Fibrous glass blanket of various colors with or without non-woven facing. No significant odor.

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Product is stable. Hazardous polymerization will not occur.
REACTIVITY:	This product is not reactive.
HAZARDOUS DECOMPOSITION PRODUCTS:	Decomposition products are those expected from any organic material and are mainly derived from pyrolysis or burning of the resin.

SECTION 11: TOXICOLOGICAL AND EPIDEMIOLOGICAL DATA

ACUTE EFFECTS:	The fibers from this product are mechanical irritants and may cause transitory irritation to exposed areas such as eyes, skin and upper respiratory passages.
CHRONIC EFFECTS:	IARC reclassified fiberglass wool as Group 3 (not classifiable as to its carcinogenicity to humans) based on current human and animal research that shows no association between inhalation exposure and development of respiratory disease (IARC Monographs Vol. 81 (2002)). ACGIH and NTP have not reviewed the IARC reclassification of fiberglass wool.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY:	This product has not been tested.
--------------	-----------------------------------

SECTION 13: DISPOSAL CONSIDERATIONS

SUMMARY:	This product is not regulated as a hazardous waste by the U.S. Environmental Protection Agency (EPA) under Resource Conservation Act (RCRA) regulations. Comply with local and state regulations for disposal. If unsure of these regulations, contact local Public Health Department or the local office of the EPA.
----------	---

SECTION 14: TRANSPORT INFORMATION

SUMMARY:	This product is not regulated as a hazardous material for transport.
----------	--



SECTION 15: REGULATORY INFORMATION

FEDERAL REGULATIONS: This product is not classified as hazardous under SARA 311/312.
ENVIRONMENTAL

REGULATIONS: This product and its components are listed in the Toxic Substances Control Act Inventory (TSCA 8(b)).

SECTION 16: OTHER INFORMATION

For additional information concerning this product, contact:

Trelleborg Applied Technologies

Trinity Park, Randall Way, Retford, DN22 7AX, UK

Telephone: +44 (0) 1777 712500 Fax: +44 (0) 1777 707001

appliedtechnologies@trelleborg.com

www.trelleborg.com/applied-technologies