




) OXRUR6HDO ² ,QGXVWULDO *UDGH
 *DVNHV VKHHW PDQXIDFWXUHG IURP D EOHQG RI ÀXRURHODVWRPHU SRO
 DSSOLFDWLRQV WKDW UHTXLUH f) VHUYLFH WHPSHUDWXUH DQG JRRG FK

3K\VLFDQ 3URSHU\	7HVW 0HWKRG	7\SLFDQ 9DOXH
Service Temperature		W
	670;1	"
Tensile Strength	670;1	SM
Average Elongation	670;1	
6SFLFV	670	1.76

) OXRUR6HDO *DVNHV 6KHHW 6W\OHV DQG 6LJHV
 3URGXFWV VROG E\ VTXDUH \DUG RU OLQHDU \DUG [Ý ZLGWK & XVWRP VLJHV
 DUH QRW JHQHUDOO\ UHVLVWDQW WR NHWRQHV ORZ PROHFXODU ZHLJKW H

*UDGH	7KLFNQHVVVH	:LGWKV)LQLVKHV
) OXRUR6HDO	Ý Ý Ý Ý Ý	Ý RU	Ý Fabric or smooth
	Ý	Ý	Fabric or smooth
	Ý	Ý	Fabric or smooth

- + LJK 4XDOLW\ ,QGXVWULDO)DEULFVHDOGHBRUJSRVLWHV IURP
- ‡ (3'0 VKHHW UXEEHU
 - Silicone sheet rubber
 - PTFE coated fabrics and tapes
 - Silicone coated fabrics
 - Specialty belting
 - ‡)OXH GXFW H[SDQVLRQ MRLQW PDWHULDOV
 - Elastomer coated and calendered fabrics
 - Fiberglass insulation matting
 - Film and foil laminates
 - Safety clothing and welding curtain fabrics