



Product Bulletin

Item Code: FO-0020
(*comparable to VS-0060)

Description: Fluoroelastomers are advanced technology elastomers designed for extreme heat, oil and chemical resistance. Trelleborg's fluoroelastomer sheet material is especially recommended for fabrication into gaskets, seals, packings, washers, pads, shims, curtains, joints and other parts for use in severe operating conditions.

<u>Coated Fabric Property</u>	<u>Test Method</u>	<u>Typical Results</u>
Polymer	ASTM D2240	FKM
Hardness Durometer (Shore A)	Visual	60 +/- 5
Color	ASTM D751	Black
Width	ASTM D412	36" usable
Tensile Strength	ASTM D792	1200 psi
Specific Gravity		1.85

Trelleborg warrants the aforementioned product is free from defects in material and workmanship when used as recommended. Trelleborg will only replace the product that is shown to our satisfaction to be defective within 30 days of delivery without charge. Defects or damage resulting from use other than recommended or misuse of any kind are not covered by this Limited Liability. These recommendations are not to be construed as warranties of any kind. Since conditions of use are beyond the control of Trelleborg, the user assumes all risks of use. Trelleborg will not be responsible for claims beyond the purchase value of the product. No sales representative, agent or distributor is authorized to extend any guarantee or warranty beyond the above terms. All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guarantee or warranty.

*VS-0060 is an item code used by others in the rubber industry



TrelleborgECF.com



ECF@Trelleborg.com