

Certificate No: **TAP0001F7**

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Bulk Loading Hoses with Permanently Fitted Couplings

with type designation(s)

Multi-Chem Black, Green, White - Multi Oil Blue, Multi-Chem Red

Issued to

Gutteling B.V.

Rotterdam, Zuid-Holland, Netherlands

is found to comply with

DNV GL class programme DNVGL-CP-0183 - Type approval - Flexible hoses

Application:

Product(s) approved by this certificate is/are accepted for installation on vessels classed by DNV GL.

Туре:	Temperature range:	Max. working press.:	Sizes:
Multi-Chem Black, Green, White - Multi Oil Blue	-30°C to +80°C	14 bar	1",1.5",2",2.5",3",4",6",8",10" (28 mm to 250 mm)
Multi-Chem Red	-30°C to +100°C	14 bar	1",1.5",2",2.5",3",4",6",8",10" (28 mm to 250 mm)

	Head of Section
Approval Engineer: Adel Samiei	Marianne Spæren Marveng
DNV GL local station: Rotterdam	
This Certificate is valid until 2023-12-31 .	for DNV GL
issued at Høvik on 2019-01-30	6

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Form code: TA 251 Revision: 2016-12 www.dnvgl.com Page 1 of 3

Job Id: **262.1-011148-9** Certificate No: **TAP00001F7**

Product description

Flexible hose assemblies with the following constructional features:

zable hose assemblies with the following constructional reactives:								
Hose design	Multi-Oil Blue	Multi-Chem	Multi-Chem	Multi-Chem	Multi-Chem			
		Black	Green	Red	White			
Inner wire	galvanised steel	Polypropylene coated steel	stainless steel AISI 316					
Inner lining	Polypropylene fabrics			ECTFE /PTFE	Polypropylene fabrics			
Inner layer	Polypropylene fabrics and films							
Outer cover		Polypropylene						
Outer wire	galvanised steel galvanised steel/stainless st			s steel AISI 316				

End connection (to the hose): according to manufacturer's drawing listed in this certificate.

End connection (to ship): Slip-on weld flange, lapped flange, weld neck flange and TTMA fixed flange (according tyo ASME B16.5 or EN1092-1)

Coupling material: Galvanized Steel or Stainless steel AISI 316L

Hoses and couplings are manufactured by Gutteling B.V., Rotterdam, Netherlands

Application/Limitation

This certificate is valid for the specific assembly of hose and coupling type as specified, assembled and delivered by the holder (named as manufacturer) of this certificate.

The hoses may be used for transfer of chemicals as per manufacturers chemical resistance list.

The hoses may be used for temporary filling and discharge only. They are not to be permanently fitted.

The hoses covered by this certificate shall be used in accordance with manfacture's instruction manual.

The scope of approval does not cover the hose handling device(s) (padeye or lifting lugs, collars, etc.)

Hoses covered by this certificate shall not be subject to vacuum condition during operation.

Production test

Each hose covered by this certificate shall be hydrostatically tested at ambient temperature to a pressure equal to 1.5 times maximum working pressure before being placed in service.

Type Approval documentation

Drawings:

GUT/HOSE/05-22, 23, 24, 25, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 00, 01, 02, 03, 04, 05, 06, 07, 08, 09, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88

GUT/STUB/01-00, GUT/MALE NIPPLE/01-00, GUT/FERRULE/01-00, GUT/FERRULE/02-00, GUT/NIPPLE/01-00, GUT/NIPPLE/02-00, GUT/SWL NUT/03-00, GUT/SWL NUT/04-00, GUT/SWL NUT/05-00, GUT/FLANGE/01-00, GUT/FLANGE/03-00, GUT/FLANGE/02-00, GUT/FLANGE/04-00, GUT/SPL/01-00, GUT/SPL/03-00, GUT/FIT/09-00, GUT/FLANGE/05-00, GUT/FLANGE/07-00, GUT/PIPE NIPPLE/01-00, GUT/SPL/02-00

Manufacturer's test reports:

 11432421_a , 1432421_b , 11432421_c , 11432421_e , 11432421_g , 11432421_i dated 2003-09-24 witnessed by DNV.

Bend test, vacuum test, IBC code test dated 2006-08-03 witnessed by DNV.

IBC code test report dated 2003-09-032008-08-21

Renewal test dated 2010-10-13 witnessed by DNV.

Chemical resistance list version 2017-09-20

Renewal burst pressure test report witnessed by DNV GL dated 2018-11-30

Form code: TA 251 Revision: 2016-12 www.dnvql.com Page 2 of 3

Job Id: **262.1-011148-9** Certificate No: **TAP00001F7**

Tests carried out

Vacuum test, proof pressure test, impulse test, cold flexibility test, IBC-Code test, oil resistance test, burst test, bend test and change in length test, electrical conductivity

Marking of product

Each end fitting shall bear a permanent identification, showing, as a minimum:

- name of manufacturer;
- hose assembly serial number;
- internal diameter of the hose;

The hose shall be permanently marked with:

- the date of the proof pressure testing,
- its specified MAWP,
- its maximum and minimum service temperature;

Periodical assessment

For retention of the Type Approval, a DNV GL Surveyor shall perform periodical assessment after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the approval are complied with. Reference is made to DNVGL-CP-0338.

Form code: TA 251 Revision: 2016-12 www.dnvgl.com Page 3 of 3